

APPENDIX:

The Appendix includes the following item(s):

- ☐ - a terminal disclaimer
- ☐ - a 37 CFR 1.132 Declaration
- ☐ - a new or amended Abstract of the Disclosure
- ☐ - a Replacement Sheet for Figure of the drawings
- ☐ - a Substitute Specification and a marked-up copy of the
originally-filed specification
- ☒ - a verified English translation of foreign priority document

Santarelli

Rinuy, Santarelli & Cabinet Bonnet-Thirion

Conseils en Propriété Industrielle
European Patent, Trademark and Design Attorneys

Marc Santarelli ▲▲

Luc Santarelli ▲▲

Thierry Cerni ▲▲

Laurence Julien-Ross ▲▲

François Lepelletier-Beaufond ▲▲

Herbert Lowitzer ▲▲

Bruno Quantin ▲▲

Georges Foidès

Professeur Georges Bonnet

Didier Billois

Arnaud Bonnin ▲▲

Richard Combès ▲▲

Arnaud Delplanque

Sylvain Espillat

Cédric Gélus ▲▲

Michaël George ▲▲

Julie Haller

Jean-Luc Hattmann ▲▲

Piotr Kolodziejczyk

Laurent Kurtz ▲▲

Eric Le Béhan ▲▲

Karine Mikus ▲▲

Valérie Moncade ▲▲

Marie-Claude Pellegrini ▲▲

Maxime Petit ▲▲

Muriel Rosenberg ▲▲

Hélène Starkoff ▲▲

Olivier Thirion ▲▲

Christine de Tremblay ▲▲

Catherine Ulmann ▲▲

▲ Conseil en Propriété Industrielle

Intellectual Property Attorney

▲ Mandataire agréé auprès

de l'Office Européen des Brevets

European Patent Attorney

▲ Conseil européen en Marques

European Trademark Attorney

Administration

Véronique Edmond

Isabelle Mercier

Monique Touchet

Elisabeth Poulet

Secrétaire général et finance

Dominique Lilaoué

Siège social / Head office

14 avenue de la Grande-Armée

Boite Postale 737

75822 Paris Cedex 17

Tél +33 (0)1 40 55 44 43

Fax +33 (0)1 42 67 56 29

Visio Conférence +33 (0)1 58 05 06 73

E-mail contact@santarelli.com

Bureau de Marseille

146 rue Paradis

13294 Marseille Cedex 6

Tél +33 (0)4 96 30 21 10

Fax +33 (0)4 96 30 21 15

E-mail marseille@santarelli.com

Bureau de Toulouse

Bureau Impérial A

Boite Postale 188

31314 Labège Cedex

Tél +33 (0)5 61 00 75 30

Fax +33 (0)5 61 00 75 30

E-mail toulouse@santarelli.com

Title of the application:

"Optimized device for digital data communication in a microcircuit card".

Filing date :

18 Dec 2002

CERTIFIED TRANSLATION OF A FRENCH PATENT APPLICATION

I, Jeremy WALKER, translator of Cabinet Santarelli, Conseils en Propriété Industrielle, 14, avenue de la Grande Armée 75017 Paris, France, hereby certify that I am fully conversant with the English and French languages and that I am a competent translator thereof, and I further certify that to the best of my knowledge and belief the following translation is a true and accurate translation of the certified copy attached hereto of the French patent application filed under the number 0216084.

Signed on 26 January 2009



Jeremy WALKER

Issu de la fusion de Rinuy, Santarelli créé en 1977 et de Cabinet Bonnet-Thirion créé en 1852

Merge of the practices of Rinuy, Santarelli (est. 1977) and Cabinet Bonnet-Thirion (est. 1852)

Société anonyme au capital de 1.533.000 euros - N° Intracommunautaire FR 12 340 66 / 880 / VAT Identification Number FR 12 340 667 880

Société enregistrée en tant que prestataire de formation sous le N° 11 75 41005 73 - Cet enregistrement ne vaut pas agrément de l'Etat.

SIRET 340 66 / 880 00011 - Code NAF 748 k

F R E N C H R E P U B L I C

< INPI / NATIONAL INSTITUTE OF INDUSTRIAL PROPERTY logo >

< FRENCH REPUBLIC / NATIONAL INSTITUTE OF INDUSTRIAL PROPERTY watermark >

PCT/FR03/03773

REC'D 01 MAR 2004

WIPO PCT

PATENT

UTILITY CERTIFICATE – CERTIFICATE OF ADDITION**OFFICIAL COPY**

The Director General of the National Institute of Industrial Property certifies that the document appended hereto is a true copy of an application for industrial property rights filed at the Institute.

Signed at Paris on 13 JAN 2004

On behalf of the Director General
of the National Institute of
Industrial Property by the Head of
the Patents Department

< signature >

Martine PLANCHE

PRIORITY DOCUMENT

PRESENTED OR TRANSMITTED
IN ACCORDANCE WITH
RULE 17.1 a) OR b)

**NATIONAL
INSTITUTE OF
INDUSTRIAL
PROPERTY**

HEADQUARTERS
26 bis, rue de Saint-Petersbourg
75600 PARIS cedex 08
Telephone : 33 (0)1 53 04 53 04
Fax : 33 (0)1 53 04 45 23
www.inpi.fr

NATIONAL PUBLIC ESTABLISHMENT

CREATED BY THE LAW OF APRIL 10 1951

1st filing

< NIIP / NATIONAL INSTITUTE
OF INDUSTRIAL PROPERTY
logo >

PATENT OF INVENTION CERTIFICATE OF UTILITY

Intellectual Property Code - Book IV



26 bis, rue de Saint Pétersbourg - 75800 Paris Cedex 08

REQUEST FOR GRANT

page 1/2



Telephone: 33 (1) 53 04 53 04

Fax: 33 (0)1 53 04 52 65

This form is to be filed in legibly with black ink

DG 640 W / 200301

FILING OF DOCUMENTS DATE 18 DEC 2002 PLACE 75 NIIP PARIS NATIONAL REGISTRATION No. 0216084 ATTRIBUTED BY THE NIIP FILING DATE ATTRIBUTED BY THE NIIP 18 DEC 2002		1 NAME AND ADDRESS OF THE APPLICANT OR AGENT TO WHOM CORRESPONDANCE IS TO BE SENT CABINET BONNET-THIRION 12, Avenue de la Grande Armée 75017 PARIS	
Your references for this file (optional) BIF114554			
Confirmation of filing by fax		<input type="checkbox"/> No. attributed by the NIIP to the fax	
2 NATURE OF THE APPLICATION		Check one of the following four boxes	
Patent application		<input checked="" type="checkbox"/>	
Certificate of utility application		<input type="checkbox"/>	
Divisional application		<input type="checkbox"/>	
<i>Initial patent application</i>		N° _____ Date _____	
<i>or initial certificate of utility application</i>		N° _____ Date _____	
Transformation or a European patent application		<input type="checkbox"/>	
<i>Initial patent application</i>		N° _____ Date _____	
3 TITLE OF THE INVENTION (maximum of 200 characters or spaces) Optimized device for digital data communication in a microcircuit card			
4 DECLARATION OF PRIORITY OR REQUEST FOR BENEFIT OF THE DATE OF FILING OF AN EARLIER FRENCH APPLICATION		Country or organization Date _____ N° _____ Country or organization Date _____ N° _____ Country or organization Date _____ N° _____ <input type="checkbox"/> If there are other priorities, check the box and use the form "Continued"	
5 APPLICANT (Check one of the 2 boxes)		<input checked="" type="checkbox"/> Legal entity <input type="checkbox"/> Private individual	
Name or corporate name		OBERTHUR CARD SYSTEMS SA	
Forenames			
Form of incorporation		Stock Company	
Company number		_____	
APE-NAF Code		_____	
Domicile or Registered Office	Street	102, Boulevard Maiesherbes	
	Poste code and town	75017 PARIS	
	Country	FRANCE	
Nationality		FRENCH	
Telephone No. (optional)			
Fax No. (optional)			
Electronic address (optional)		<input type="checkbox"/> If there are other applicants, check the box and use the form "Continued"	

It is obligatory to fill in the 2nd page

1st filing

< NIIP / NATIONAL INSTITUTE
OF INDUSTRIAL PROPERTY
logo >

PATENT OF INVENTION CERTIFICATE OF UTILITY

REQUEST FOR GRANT
page 2/2

BR2

FILING OF DOCUMENTS DATE 18 DEC 2002 PLACE 75 NIIP PARIS NATIONAL REGISTRATION NUMBER ATTRIBUTED BY THE NIIP 0216084		Rec'd for NIIP	
6 AGENT (if appropriate) Name Forename Firm or company Power of attorney No. and/or contractual link Address Street Post code and town Country Telephone No. (optional) Fax No. (optional) Electronic address (optional)		BIF114554 / FR CABINET BONNET-THIRION 12 Avenue de la Grande Armée 75 001 17 PARIS FRANCE 01 53 81 17 00	
7 INVENTOR (S) The inventors are the applicants		The inventors are necessarily private individuals <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No: In this case provide a separate designation of inventor (s)	
8 SEARCH REPORT Immediate establishment or deferred establishment Payment of the fee in installments (in two payments)		Solely for a patent application (including a divisional or transformation) <input checked="" type="checkbox"/> <input type="checkbox"/> Only for physical persons themselves undertaking filing <input type="checkbox"/> Yes <input type="checkbox"/> No	
9 REDUCTION OF THE LEVEL OF THE FEES		Solely for private individuals <input type="checkbox"/> Required for the first time for this invention (provide a notification of non-chargeability) <input type="checkbox"/> obtained prior to this filing for this invention (provide a copy of the decision of acceptance for free assistance or indicate its reference number): AG	
10 SEQUENCES OF NUCLEOTIDES AND/OR AMINO ACIDS The electronic data carrier is appended The declaration of conformity of the list of sequences on paper with the electronic data carrier is appended If you have used the form "Continued" indicate the number of pages attached		<input type="checkbox"/> Check box if the description contains a list of sequences	
11 SIGNATURE OF THE APPLICANT OR AGENT (Name and capacity of the person signing) Bruno QUANTION N°92.1206 CABINET BONNET-THIRION < Signature >		VISA OF THE PREFECTURE OR OF THE NIIP < Illegible visa >	

The law No. 78-17 of January 6, 1978 on electronic information, files and civil liberties applies to the entries made on this form.
It ensures a right of access and of correction of the data concerning you at the NIIP.

1st filing

1

The present invention relates to a microcircuit card.

To be more precise, the invention is directed to a microcircuit card adapted to:

5 - process a relatively voluminous stream of digital data exchanged with a device external to the card, and

 - implement security procedures, for example functions for verifying the integrity of the digital data exchanged with the external device or cryptographic functions for authenticating a user of the card.

10 Thus the invention may be used to decompress an encrypted digital data stream.

 In one prior art architecture of this kind of card, the digital data received from an input-output port of the microcircuit card is read by a microprocessor and processed as and when it is received. The microprocessor effects the security checks referred to above as it receives digital data.

15 A major problem with the above architecture is that the digital data stream that can be exchanged by the card is limited by the frequency of the microprocessor (which is generally of the order of 4 MHz in the case of microcircuit cards known in the state of the art).

20 In other fields of electronics, to alleviate the limits associated with the frequency of a microprocessor, the transfer of data at high bit rates is often effected by means of dedicated direct memory access (DMA) components. These DMA components are programmed by a microprocessor to effect a predetermined transfer, for example between an input-output port and a memory, the microprocessor not handling the transfer as such.

25 Unfortunately, these DMA components are dedicated to transferring data and are unable to effect processing of data during its transfer. They are therefore not adapted, a priori, for transferring sensitive data necessitating security operations, as is the case for the microcircuit cards cited above.

30 The invention aims, by overcoming this apparent incompatibility, to enable transfer of a voluminous or fast secure data stream in a microcircuit card

1st filing

2

whilst maintaining a high security level thanks to an original association of a processor and direct memory access.

To this end, it provides a microcircuit card including:

- input-output means for digital data;
- 5 - processing means for processing this data; and
- stream control means.

The microcircuit card is characterized in that the processing means include:

- transfer means for transferring said digital data between the input-output means and a storage area; and
- 10 - communication means for communicating with the stream control means security data obtained from the digital data, the stream control means being adapted to control the transfer of the digital data by the transfer means taking into account said security data.

Accordingly, the data received from the communication port is
15 transferred by the transfer means to a storage area, the stream of this transfer being not limited by the speed of the stream control means.

Moreover, during this transfer, security data obtained from the digital data is communicated by the processing means to the stream control means, the security data stream received by the stream control means being limited
20 and in any event much less voluminous than the digital data stream received by the card.

The stream control means, consisting, for example, of a processor, are then in a position by using this security data to effect the operations necessary for controlling the transfer means to guarantee compliance with
25 security constraints.

The invention therefore enables the digital data stream processed by the microcircuit card to be more voluminous whilst maintaining the security level of a conventional card.

In a first variant embodiment of the microcircuit card of the invention,
30 the security data referred above consists at least in part of a portion of said digital data transferred by the card.

1st filing

3

5 In a preferred embodiment of this first variant, the security data includes authentication data for authenticating a portion of the digital data received by the card, the stream control means being adapted to verify the validity of said digital data on the basis of this authentication data and to control the transfer as a function of the result of this verification.

In known manner, if the stream control means determine that the authentication data is not valid when the card receives digital data transmitted by an external device, this means that the digital data was not sent by an authorized sender.

10 In this situation, the stream control means may take a predetermined measure, such as blocking use of the card or sending an error message.

In a preferred embodiment, to guarantee secure use of the card, the stream control means command the transfer means to stop the transfer of digital data if the authentication data is not valid.

15 Thus the card is able to receive a voluminous data stream, only a portion of that data being communicated to the stream control means to guarantee the required security.

20 In a second variant embodiment, the processing means are adapted to insert into the security data a result of processing calculated from the digital data.

The processing result may, for example, be the result of a step of verifying the aforementioned authentication data by calculation means included in the processing means, for example cryptographic means of the microcircuit card. This result is then taken account of by the stream control means to verify the integrity of the digital data and to control its transfer by the transfer means accordingly.

This authentication step may consist in verifying a signature, for example using a cryptographic key and a hashing function in accordance with an algorithm of MD4, MD5 or SHA-1 type.

30 In this variant, the stream control means effect the steps of verifying the authentication data. They may then implement a predetermined measure in

1st filing

4

the event of fraudulent misuse of the card, such as stopping the transfer of the digital data or blocking the use of the card.

5 In a preferred embodiment, the stream control means control the transfer of digital data by modifying at least one operating parameter of the transfer means.

For example, this operating parameter is a storage address of the digital data in the storage area.

10 Accordingly, if the occupancy of a first range of the storage area is above a predetermined threshold, the stream control means can set the parameters of the transfer means so that the digital data received by the transfer means is stored at that address.

15 The parameter cited above may also be a parameter for selecting the protocol for communication between the input-output means and the storage area. This communication protocol can be, for example, adapted to transferring secure data.

In different variant embodiments of the microcircuit card of the invention, the processing means include a data compression unit, a data decompression unit, a data encryption unit or a data decryption unit.

20 In another variant embodiment, the stream control means are further adapted to obtain directly from the input-output means preliminary data that is taken account of by the stream control unit to authorize or refuse the transfer of the digital data by the transfer means.

In one particular embodiment of this variant, this preliminary data includes authentication data.

25 This embodiment provides an additional level of security, for example through checking an authentication code prior to the transfer of the digital data proper. Unlike security data, this authentication code is typically verified once only at the start of a transfer session. It may require a longer calculation time, and therefore employ a complex authentication algorithm providing a higher
30 level of security.

In another preferred embodiment, this preliminary data includes a

1st filing

5

storage address of the digital data that will be transferred by the transfer means. In this preferred embodiment, this preliminary data may further include data for authenticating the storage address, in order to guarantee that the storage address has not been supplied by an unauthorized user.

5 In a particularly advantageous embodiment, the microcircuit card further includes regulation means adapted to modify a clock frequency applied to the processing means as a function of said security data.

This feature then allows to limit the electrical power consumption of the microcircuit card if the transfer of digital data by the transfer means must be interrupted.

10 The invention will be better understood and other advantages of the invention will become more clearly apparent in the light of the following description of a microcircuit card of the invention, which description is given by way of example only and with reference to the appended drawing, in which:

- 15
- figure 1 is a block diagram of a prior art microcircuit card;
 - figure 2 is a block diagram analogous to figure 1 showing one possible embodiment of a microcircuit card of the invention; and
 - figure 3 shows an example of security data conforming to the invention.

20 The prior art microcircuit card 10 shown in figure 1 includes primarily a processor CPU associated conventionally with a number of memories (of RAM, ROM, or EEPROM type), processing means 12 and input-output means 14 connected, for example, to a terminal.

25 The processing means 12 include a calculation unit 13 adapted to perform the actual processing of the digital data, that is to say for example operations of compression, decompression, encryption or decryption of these data.

30 In a preferred embodiment, the input-output means 14 enable the microcircuit card 10 to communicate with an external terminal or electronic entity essentially comprising a UART (universal asynchronous receiver-transmitter).

1st filing

6

The input-output means 14 may also be adapted to implement standard communication protocols known to the person skilled in the art, for example the protocols referred to as "T=0", "T=1" (ISO 7816), USB, FireWire or I2C.

5 According to the prior art, when microcircuit card 10 receives via the UART digital data that is to be processed by the calculation unit 13 of the processing means 12, the UART sends an interrupt message to the processor CPU. The processor CPU then reads a register of the UART and copies the data into the RAM.

10 The processor CPU then initializes the processing means 12, reads the data to be processed in the RAM and copies it into a register 16 of the processing means 12.

15 In order to be communicated to the external terminal, the result calculated by the processing means 12 is then read by the processor CPU in the register 16 and copied into the UART register by the processor CPU.

This mode of operation is not favorable to the processing of high bit-rate digital data by the microcircuit card 10. Because the intermediate operation effected by the processor CPU of copying digital data into the RAM area before it is processed by the processing means 12 is particularly penalizing.

20 However, the requirement is to increase the processing power of this kind of microcircuit card to process voluminous and continuous data streams in real time.

25 For example, it might be required to be able to carry out real time decryption of digital data representative of sound. Such data is compressed to the MP3 standard and transmitted at a bit rate of 128 kbit/s. The microcircuit card responsible for real time decryption therefore needs to be able to receive and process information at a high bit rate.

A microcircuit card conforming to the invention and solving the above problem is described next with reference to figure 2.

30 In accordance with the present invention, the processing means 12 include means DMA for transferring digital data between the communication

1st filing

7

port 14 and a storage area 18.

In the figure 2 example described here, the storage area 18 is a random access memory RAM.

In other embodiments, the storage area 18 may be selected from various types of rewritable memory, for example Flash memory, EEPROM type memory or a hard disk.

In another variant, the storage area 18 is a port of the calculation unit 13 of the processing means 12.

In the preferred embodiment described here, the transfer means DMA include a dedicated electronic direct memory access (DMA) component known to the person skilled in the art.

In known manner, this component is programmed by writing parameters into configuration registers.

By way of non-limiting example, such parameters include the address of a port of the input-output means 14, the address of a range of the storage area 18 in which the digital data must be stored, and parameters representative of a criterion for stopping the transfer.

Be this as it may, the microcircuit card of the invention further includes stream control means 26 adapted to control the transfer of the digital data by the transfer means DMA.

In particular, if the digital data must be transferred to a storage area 18 of EEPROM type, the stream control means 26 are adapted to control a voltage generator or any other means of applying a sufficient electrical voltage to the EEPROM for it to be accessible in write mode.

In the embodiment described with reference to figure 2, the stream control means 26 consists of a processor CPU conventionally associated with these different memories (RAM, ROM, EEPROM), as in the case of figure 1.

The setting of parameters of the transfer means DMA by the stream control means 26 is represented diagrammatically in figure 2 by the signals 20.

In accordance with the present invention, the processing means 12 also include means 22 for communication between its calculation unit 13 and

1st filing

8

the stream control means 26.

The communication means 22 enable the exchange between the processing means 12 and the stream control means 26 of security data obtained from digital data DATA transferred by the transfer means DMA.

5 Chronologically, once the transfer means DMA have been programmed by the stream control means 26, by means of the signals 20, the transfer means DMA effect the transfer of the digital data between the input-output means 14 and the storage area 18. The calculation unit 13 of the processing means 12 then obtains security data DATA_CTRL from the digital
10 data DATA stored in the storage area 18 and communicates it to the stream control means 26 via the communication means 22.

Figure 3 shows one example of the security data DATA_CTRL used in a preferred embodiment.

15 The security data DATA_CTRL includes a digital data portion P1 and authentication data AUTH calculated from the digital data of the portion P1.

In a first variant, the authentication data AUTH forms a signature of the portion P1. This is typically a data portion P1 to which a prior art hashing function (e.g. an MD4, MD5 or SHA-1 function) and then an encryption algorithm have been applied. A symmetrical key encryption algorithm may be
20 used for this purpose, such as the data encryption standard (DES) algorithm, or an asymmetric key algorithm such as the Rivest, Shamir and Adelman (RSA) algorithm.

In this variant, on receiving this security data DATA_CTRL, the stream control means 26 first decrypt the signature AUTH using the decrypting
25 key and obtain a first result HASH1. The stream control means 26 then apply the hashing function to the portion P1 and obtain a second result HASH2.

The stream control means 26 then compare the first result HASH1 and the second result HASH2.

30 In a preferred embodiment of this first variant, if these results HASH1 and HASH2 are different, the stream control means 26 send a stop signal to command stopping of the transfer of digital data.

1st filing

9

In the preferred embodiment, the processing means 12 insert into the security data DATA_CTRL a result of processing of the digital data DATA by the calculation unit 13.

5 This processing result is, for example, the address at which a portion of the digital data DATA has been stored in the storage area 18 by the transfer means DMA, the stream control means 26 then being adapted to read the data of that portion, verify its validity, and control the transfer of the digital data DATA by the transfer means DMA as a function of the result of this verification.

10 In an embodiment in which the processing means 12 include cryptographic means 13, this processing result is the result obtained by the cryptographic unit 13 in a step of authenticating the digital data DATA.

In a variant, the processing result is the result obtained by the cryptographic means 13 in a step of verifying a signature of the digital data DATA.

15 For example, this verification step may consist in decrypting the data AUTH using an RSA algorithm to obtain a result similar to the first result HASH1.

20 In a preferred embodiment, the stream control means 26 are further adapted to obtain preliminary data directly from the input-output means 14 over the data path 24 represented in figure 2.

In a variant, the preliminary data is obtained by the stream control means 26 from a second input-output port, for example using the protocol referred to as "T=0" (ISO 7816), the input-output means 14 being reserved for the transfer of the digital data DATA by the transfer means DMA.

25 The data path 24 may also be a bidirectional data path used by the stream control means 26 to communicate information to a device external to the microcircuit card. This information may, for example, consist of an error message sent by the stream control means 26 if they detect the presence of erroneous digital data on the basis of the security information.

30 This information may also consist of a data stream leaving the microcircuit card that is the result of the processing by the processing means 12

1st filing

10

of the digital data DATA received by the card.

This preliminary data includes, for example, authentication data PASSWD and, be this as it may, is taken into account to control the transfer of digital data by the transfer means DMA.

5 Accordingly, if the authentication data PASSWD does not conform to a predetermined control rule, for example, which rule may be stored in the ROM, the stream control means 26 do not program the transfer means DMA to transfer the digital data between the input-output means 14 and the storage area 18.

10 The preliminary data preferably includes a digital data storage address.

In a variant, the microcircuit card includes regulation means PLL adapted to modify a clock frequency applied to the processing means 12 as a function of the control data DATA_CTRL.

15 These regulation means PLL may consist of a phase-locked loop (PLL) component known by the person skilled in the art and used to derive signals at various clock frequencies from a signal from an external clock (not shown).

20 In the preferred embodiment, these regulation means PLL are controlled by the stream control means 26 in order to adjust the electrical power consumption of the processing means 12 as a function of the stream of digital data DATA.

25 In the selected embodiment, the transfer means DMA may be unidirectional or bidirectional. The invention applies in particular to controlling the transfer of encrypted digital data DATA from the storage area 18 to the input-output means 14.

1st filing

11

CLAIMS

1. Microcircuit card including:

- input-output means (14) for digital data (DATA);
- processing means (12) for processing this data; and
- stream control means (26),

the microcircuit card being characterized in that the processing means (12) include:

- transfer means (DMA) for transferring said digital data (DATA) between the input-output means (14) and a storage area (18); and

- communication means (20) for communicating with the stream control means (26) security data (DATA_CTRL) obtained from said digital data (DATA),

the stream control means (26) being adapted to control the transfer of the digital data (DATA) by the transfer means (DMA) taking into account said security data (DATA_CTRL).

2. Microcircuit card according to claim 1, characterized in that said security data (DATA_CTRL) consists at least in part of a portion of said digital data (DATA).

3. Microcircuit card according to claim 2, characterized in that said security data (DATA_CTRL) includes authentication data (AUTH) for authenticating a portion (P1) of the digital data received by the card, the stream control means (26) being adapted to verify the validity of said digital data (DATA) on the basis of this authentication data (AUTH) and to control said transfer as a function of the result of this verification.

4. Microcircuit card according to any one of claims 1 to 3, characterized in that said processing means (12) are adapted to insert into said security data (DATA_CTRL) a result of processing said digital data (DATA).

5. Microcircuit card according to claim 4, characterized in that said processing result is the result of a step of authenticating said digital data.

6. Microcircuit card according to any one of claims 1 to 5, characterized in that the stream control means are adapted to modify at least

1st filing

12

one operating parameter of said transfer means (DMA).

5 7. Microcircuit card according to claim 6, characterized in that said parameter is chosen between an address of said storage area (18) and a parameter for selecting a protocol for communication between the input-output means (14) and the storage area (18).

8. Microcircuit card according to any one of claims 1 to 7, characterized in that said processing means (12) include a data compression unit (13), a data decompression unit, a data encryption unit or a data decryption unit.

10 9. Microcircuit card according to any one of claims 1 to 8, characterized in that said stream control means (26) are adapted to stop the transfer of the digital data (DATA) by said transfer means (DMA) if they detect the presence of invalid authentication data in said digital data (DATA) on the basis of said security data (DATA_CTRL).

15 10. Microcircuit card according to any one of claims 1 to 9, characterized in that the stream control means (26) are further adapted to obtain preliminary data directly from the input-output means (14), the stream control means (26) also taking account of the preliminary data in authorizing or refusing the transfer of the digital data (DATA) by the transfer means (DMA).

1st filing

Amended on May 6, 2003

13

11. Microcircuit card according to claim 10, characterized in that said preliminary data includes authentication data (PASSWD).

5 13. Microcircuit card according to claim 11 or claim 12, characterized in that said data includes a storage address for said digital data.

14. Microcircuit card according to any one of claims 1 to 13, characterized in that it further includes regulation means (PLL) adapted to modify a clock frequency applied to the processing means (12) as a function of said security data (DATA_CTRL).

10 15. Microcircuit card according to any one of claims 1 to 14, characterized in that said transfer means (DMA) include a DMA component.

received on May 6, 2003

13

11. Microcircuit card according to claim 10, characterized in that said preliminary data includes authentication data (PASSWD).



5 12. Microcircuit card according to claim 10 or claim 11, characterized in that said data includes a storage address for said digital data.

13. Microcircuit card according to any one of claims 1 to 12, characterized in that it further includes regulation means (PLL) adapted to modify a clock frequency applied to the processing means (12) as a function of said security data (DATA_CTRL).

10 14. Microcircuit card according to any one of claims 1 to 13, characterized in that said transfer means (DMA) include a DMA component.

1st filing

1 / 1

**FIGURE 1****FIGURE 2****FIGURE 3**

received on 29 January 2003



Patents Department

28 bis, rue de Saint-Petersbourg - 75003 Paris Cedex 05

PATENT OF INVENTION
CERTIFICATE OF UTILITY
 Intellectual Property Code - Book VI



DESIGNATION OF INVENTOR(S) Page N° ... / ...
 (If the applicant is not the inventor or sole inventor)

Telephone: 33 (1) 53 04 53 04

Facsimile: 33 (0)1 53 04 52 65

This form is to be filled in legibly in black ink

DB 113 W / 300301

Your references (Optional)		BIF114554/FR
NATIONAL REGISTRATION NUMBER		
TITLE OF THE INVENTION (maximum of 200 characters or spaces) Optimized device for digital data communication in a microcircuit card		
THE APPLICANT(S) OBERTHUR CARD SYSTEMS S.A.		
DESIGNATE AS INVENTORS : (State "Page N° 1/1" at top right. If there are more than three inventors, use an identical form, number each page and give the total number of pages.)		
1	Name	GOUESSANT
	Forenames	Hervé
Address	Street	102, Boulevard Maiesherbes
	Post code and town	91410 VITRY SUR SEINE, France
		Company to whom belongs (optional)
2	Name	JAYET
	Forenames	Stéphane
Address	Street	25 Allée des Noisetiers
	Post code and town	91510 BEAUCHAMP, France
		Company to whom belongs (optional)
3	Name	
	Forenames	
Address	Street	
	Post code and town	
		Company to whom belongs (optional)
DATE AND SIGNATURE(S) OF THE APPLICANT(S) OR AGENT (Name and capacity of the person signing)		
28 January 2003 Bruno QUANTIN N°92.1206 CABINET BONNET-THIRION < Signature >		

The law No. 78-17 of January 6, 1978 on electronic information, files and civil liberties applies to the entries made on this form.
 It ensures a right of access and of correction of the data concerning you at the INPI.

PCT Application
PCT/FR2003/003773

